

BATTERY RECOGNITION CHART

12V & 24V

6 Cell Battery (12 Volt)

Model	AH	Length	Width	Height	Model	AH	Length	Width	Height	Model	AH	Length	Width	Height
6-85-5	170	12.38	6.56	22.50	6-85-15	595	17.75	12.75	22.55	6-85-23	935	26.81	12.81	22.55
6-85-7	255	16.88	6.50	22.55	6-85-15	595	35.13	6.50	22.55	6-85-23	935	38.13	9.13	22.55
6-85-9	340	21.50	6.50	22.55	6-85-15	595	35.13	7.75	22.55	6-85-25	1020	29.13	12.81	22.55
6-85-11	425	26.00	7.75	22.50	6-85-17	680	20.06	12.75	22.55	6-85-27	1105	31.38	12.81	22.55
6-85-11	425	19.00	9.00	22.50	6-85-17	680	38.13	7.75	22.55	6-85-29	1190	33.63	12.81	22.55
6-85-11	425	26.00	9.56	22.50	6-85-17	680	38.13	6.50	22.55	6-85-31	1275	35.88	12.81	22.55
6-85-11	425	30.50	7.75	22.50	6-85-19	765	38.13	7.75	22.55	6-85-33	1360	38.13	12.81	22.55
6-85-13	510	30.50	7.75	22.50	6-85-19	765	22.38	13.00	22.55	6-100-13	600	30.50	7.75	26.24
6-85-13	510	30.63	6.69	22.50	6-85-21	850	24.63	12.81	22.55	6-125-13	750	30.50	7.75	30.50
6-85-13	510	15.50	12.75	22.55										

12 Cell Battery (24 Volt)

Model	AH	Length	Width	Height	Model	AH	Length	Width	Height	Model	AH	Length	Width	Height
12-85-5	170	24.88	6.50	22.50	12-125-11	625	26.13	12.81	30.50	12-85-17	680	39.63	13.00	22.50
12-85-5	170	24.88	7.75	22.50	12-125-11	625	31.88	11.00	30.50	12-85-17	680	22.50	19.50	22.50
12-85-7	255	33.63	6.50	22.50	12-125-11	625	38.00	9.00	30.50	12-125-17	1000	26.63	19.23	30.50
12-85-7	255	25.19	8.56	22.50	12-125-11	625	19.38	17.38	30.50	12-125-17	1000	38.13	13.50	30.50
12-125-7	375	33.63	6.50	30.50	12-85-13	510	30.56	12.81	22.50	12-125-17	1000	39.63	13.00	30.50
12-125-7	375	25.19	8.56	30.50	12-85-13	510	25.50	15.50	22.50	12-125-17	1000	25.50	19.50	30.50
12-85-9	340	19.25	14.63	22.50	12-85-13	510	35.75	11.75	22.50	12-85-19	765	38.13	14.75	22.50
12-85-9	340	25.13	10.81	22.50	12-85-13	510	38.13	10.50	22.50	12-85-19	765	29.63	19.25	22.50
12-85-9	340	22.25	13.00	22.50	12-85-13	510	20.50	19.13	22.50	12-85-19	765	44.13	12.88	22.50
12-85-9	340	38.00	7.50	22.50	12-125-13	750	30.56	12.81	30.50	12-125-19	1125	38.13	14.75	30.50
12-85-9	340	42.63	6.50	22.50	12-125-13	750	25.50	15.50	30.50	12-125-19	1125	29.63	19.25	30.50
12-85-9	340	28.63	10.13	22.50	12-125-13	750	35.75	11.75	30.50	12-125-19	1125	44.13	12.88	30.50
12-125-9	500	19.25	14.63	30.50	12-125-13	750	38.13	10.50	30.50	12-85-21	850	32.63	19.23	22.50
12-125-9	500	25.13	10.81	30.50	12-125-13	750	20.50	19.13	30.50	12-85-21	850	38.13	16.44	22.50
12-125-9	500	22.25	13.00	30.50	12-85-15	595	25.63	17.75	22.50	12-85-21	850	25.63	24.50	22.50
12-125-9	500	38.00	7.50	30.50	12-85-15	595	35.13	12.88	22.50	12-85-23	935	35.63	19.25	22.50
12-125-9	500	42.63	6.50	30.50	12-85-15	595	38.13	12.00	22.50	12-85-23	935	38.13	21.00	22.50
12-125-9	500	28.63	10.13	30.50	12-125-15	875	25.63	17.75	30.50	12-85-25	1020	38.13	21.00	22.50
12-85-11	425	25.38	13.13	22.50	12-125-15	875	35.13	12.88	30.50	12-85-25	1020	29.25	25.75	22.50
12-85-11	425	26.13	12.81	22.50	12-125-15	875	38.13	12.00	30.50	12-85-27	1105	38.13	21.00	22.50
12-85-11	425	31.88	11.00	22.50	12-125-15	875	36.00	14.00	30.50	12-85-27	1105	41.75	19.50	22.50
12-85-11	425	38.00	9.00	22.50	12-85-17	680	26.63	19.23	22.50	12-85-29	1190	44.63	19.25	22.50
12-85-11	425	19.38	17.38	22.50	12-85-17	680	38.13	13.50	22.50	12-85-31	1275	47.63	19.25	22.50
12-125-11	625	25.38	13.13	30.50						12-85-33	1360	50.63	19.22	22.50

BATTERY RECOGNITION CHART

36V & 48V

18 Cell Battery (36 Volt)

Model	AH	Length	Width	Height	Model	AH	Length	Width	Height	Model	AH	Length	Width	Height
18-85-9	340	37.75	11.13	22.50	18-125-13	750	31.56	20.44	30.50	18-85-19	765	36.88	25.63	22.50
18-85-9	340	25.44	17.75	22.50	18-125-13	750	38.06	15.38	30.50	18-85-19	765	31.88	29.63	22.50
18-85-9	340	22.50	19.14	22.50	18-125-13	750	25.75	25.50	30.50	18-85-19	765	35.75	25.50	22.50
18-85-9	340	39.75	13.81	22.50	18-125-13	750	37.75	15.44	30.50	18-85-19	765	38.13	22.31	22.50
18-125-9	500	37.75	11.13	30.50	18-85-15	595	31.81	23.56	22.50	18-85-19	765	44.25	19.44	22.50
18-125-9	500	25.44	17.75	30.50	18-85-15	595	29.31	25.56	22.50	18-125-19	1125	36.88	25.63	30.50
18-125-9	500	22.50	19.13	30.50	18-85-15	595	35.31	19.25	22.50	18-125-19	1125	31.88	29.63	30.50
18-125-9	500	39.75	13.81	30.55	18-85-15	595	38.13	17.69	22.50	18-125-19	1125	35.75	25.50	30.50
18-85-11	425	26.13	19.06	22.50	18-125-15	875	31.81	23.56	30.50	18-125-19	1125	38.13	22.31	30.50
18-85-11	425	25.55	21.88	22.50	18-125-15	875	29.31	25.56	30.50	18-125-19	1125	44.25	19.44	30.50
18-85-11	425	30.50	17.94	22.50	18-125-15	875	35.31	19.25	30.50	18-85-21	850	38.13	24.63	22.50
18-85-11	425	38.13	13.13	22.50	18-125-15	875	38.13	17.69	30.50	18-85-21	850	32.75	31.81	22.50
18-125-11	625	26.13	19.06	30.50	18-85-17	680	33.06	25.56	22.50	18-85-21	850	39.00	25.63	22.50
18-125-11	625	25.55	21.88	30.50	18-85-17	680	38.13	20.06	22.50	18-85-23	935	33.14	32.06	22.50
18-125-11	625	30.50	17.94	30.50	18-85-17	680	31.81	26.56	22.50	18-85-23	935	38.13	26.88	22.50
18-125-11	625	38.13	13.13	30.50	18-85-17	680	39.75	19.44	22.50	18-85-25	1020	38.13	29.13	22.50
18-85-13	510	30.63	19.13	22.50	18-85-17	680	32.75	26.00	22.50	18-85-25	1020	36.06	32.69	22.50
18-85-13	510	31.56	20.44	22.50	12-125-17	1000	33.06	25.26	30.50	18-85-27	1105	38.13	31.38	22.50
18-85-13	510	38.06	15.38	22.50	12-125-17	1000	38.13	20.06	30.50	18-85-29	1190	38.13	35.63	22.50
18-85-13	510	25.75	25.50	22.50	12-125-17	1000	31.81	26.56	30.50	18-85-31	1275	38.13	36.13	22.50
18-85-13	510	37.75	15.44	22.50	12-125-17	1000	39.75	19.44	30.50	18-85-33	1360	38.38	38.11	22.50
18-125-13	750	30.63	19.13	30.50	12-125-17	1000	32.75	26.00	30.50					

24 Cell Battery (48 Volt)

Model	AH	Length	Width	Height	Model	AH	Length	Width	Height	Model	AH	Length	Width	Height
24-85-7	255	33.38	14.13	22.50	24-125-11	625	26.00	25.25	30.50	24-85-19	765	38.13	29.63	22.50
24-85-9	340	38.06	14.50	22.50	24-125-11	625	38.06	20.56	30.50	24-85-21	850	38.13	32.63	22.50
24-85-9	340	32.00	18.38	22.50	24-85-13	510	30.63	25.38	22.50	24-85-23	935	38.13	35.56	22.50
24-85-9	340	29.25	19.25	22.50	24-85-13	510	37.75	20.44	22.50	24-85-25	1020	38.75	38.13	22.50
24-125-9	500	38.06	14.50	30.50	24-125-13	750	30.63	25.38	30.50	24-85-27	1105	42.00	38.50	22.50
24-125-9	500	32.00	18.38	30.50	24-125-13	750	37.75	20.44	30.50	24-85-29	1190	44.75	38.13	22.50
24-125-9	500	29.25	19.25	30.50	24-85-15	595	38.06	23.63	22.50	24-85-31	1275	47.75	38.13	22.50
24-85-11	425	38.06	17.75	22.50	24-85-15	595	32.00	29.50	22.50	24-85-33	1360	50.75	38.13	22.50
24-85-11	425	26.00	25.25	22.50	24-85-15	595	35.13	25.44	22.50					
24-85-11	425	38.06	20.56	22.50	24-85-17	680	38.06	26.56	22.50					
24-125-11	625	38.06	17.75	30.50	24-85-17	680	39.63	25.66	22.50					